

# Model ZW215FP - Fire Pump Suction Control Valve

## Control Valve Order Form



Customer:	Date:
Contact:	Email:
Telephone/Fax:	Ref. P. O.

### Required Valve Information

Quantity: \_\_\_\_\_

All returns are subject to a restocking/refurbishing fee. Contact Customer Care for details on return policies.

**Size:** (Check one)    2"    2-1/2"    3"    4"    6"    8"    10"

**Caution:** The recommended installation orientation for ACVs is horizontal, with the valve cover up. 6" and larger valves should only be installed horizontally, with the valve cover up, due to the difficulty of properly bleeding air out of the cover and performing maintenance on valves installed in the vertical orientation.

**Valve body is ductile iron, epoxy coated**

### Body Options:

- Check one
- Standard - Full Port Globe Body
  - "A" Option - Angle Style Body

### End Connections:

- Check one
- Standard - ANSI Class 150 Flanges (2" - 10")
  - "G" Option - IPS Grooved (2" - 10")
  - "TH" Option - NPT Threaded (2" - 3")
  - "Y" Option \* - ANSI Class 300 Flanges (2" - 10")



### Main Valve Options:

- Optional
- Standard - Stainless Steel Seat, Seal Ring Retainer, and Stem Guide
  - "Z2" Option - Stainless Steel Dry Position Indicator (Replaces ZPI Visual Position Indicator)

### Pilot Options:

- Standard - "Wye" Type Strainer, Visual Position Indicator, and Sensing Line Bleed Valve
  - Standard - PV-RLF Pilot (10 - 30 psi)
- 
- Check one
- Standard - Copper Tubing and Brass Fittings
  - "SP" Option \* - All Stainless Steel Pilotry (replaces all Brass Fittings, Pilot Valve & Copper Tubing)
- 
- Optional
- "RV" Option - Pilot on Reverse Side

### FM® Approved

\*Adder to standard price applies

1747 Commerce Way  
Paso Robles, CA 93446  
Phone: 855-663-9876  
Fax: 805-237-7197

Customer Service Representatives available  
Monday through Friday 5:30 a.m. to 5:00 p.m., PST  
Fax completed forms to 805-237-7197, attention: Sales  
Call 855-663-9876, wilkinscs@zurn.com  
or visit us online at www.zurn.com

