MODEL ZW218 - Slow Close Check Valve **Control Valve Order Form**



Customer:	Date:
Contact:	Email:
Telephone/Fax:	Ref. P. O.

Required Valve Information

Quantity:	0	_	424.		
	QU	lan	τιτ	/:	

All returns are subject to a restocking/refurbishing fee. Contact Customer Care for details on return policies.

Valve body is ductile iron, epoxy coated

Size: (Check one)	1-1/4″	1-1/2″	2″	2-1/2″	3″	4″	6″	8″	10″	12″	14″	16″
-------------------	--------	--------	----	--------	----	----	----	----	-----	-----	-----	-----

Caution: The recommended installation orientation for ACVs is horizontal, with the valve cover up. 6" and larger valves should only be installed horizontally, with the valve cover up, due to the difficulty of properly bleeding air out of the cover and performing maintenance on valves installed in the vertical orientation.

Function Options:

Standard

Opening and Closing Speed Control Valves, Check Valves

Body Options:

Charle	Standard	-	Full Port Globe Body
Check one	"A" Option	-	Angle Style Body (1-1/4″ - 10″)
	"R" Option	-	Reduced Port Body (3" - 10" Flanged only)

End Connections:

	Standard	-	ANSI Class 150 Flanges (1-1/2″ - 16″)
Check	"G" Option	-	IPS Grooved (1-1/2″ - 10″)
one	"TH" Option	-	NPT Threaded (1-1/4" - 3")
	"Y" Option *	-	ANSI Class 300 Flanges (1-1/2″ - 16″)

DIRECTION OF FLOW

Main Valve Options:

M	Standard -	Stainless Steel Seat, Seal Ring Retainer, and Stem Guide
	"Z" Option *1 -	Visual Position Indicator
	"SO" Option *1 -	Limit Switch Open Trip
	"SC" Option *1 -	Limit Switch Closed Trip
	"SD" Option *1 -	Limit Switch Dual Trip
		"Z" Option *1 - "SO" Option *1 - "SC" Option *1 -

Pilot Options:

Check	Standard	-	Copper Tubing and Brass Fittings
all that	"SP" Option*	-	All Stainless Steel Pilotry (replaces all Brass Fittings, Pilot Valve & Copper Tubing.
apply			"GL" Option included)
	"SH" Option*	-	Stainless Steel Braided Hoses (replaces Copper Tubing)

*Adder to standard price applies ¹Limit switch and position indicator options cannot be combined

1747 Commerce Way Paso Robles, CA 93446 Phone: 855-663-9876 Fax: 805-237-7197

Customer Service Representatives available Monday through Friday 5:30 a.m. to 5:00 p.m., PST Fax completed forms to 805-237-7197, attention: Sales Call 855-663-9876, wilkinscs@zurn.com or visit us online at www.zurn.com



Document# Rev. K OF-ZW218