


## Z9A-MA MALE THREAD ADAPTER

### Engineering Specification:

ASTM-F1412, F.R.P.P. - 210  
 ZURN Z9A-MA MALE ADAPTER – Flame-retardant polypropylene male adapter fitting assembly.  
 Use Teflon tape on threads.



### Options:


-F Fusion Lock; -M Mechanical Seal; -S Stab•Lock Seal

Model No.	Dimensions in Inches [mm]		
	Nom. Pipe Size	E	L
Z9A-MA-112	1-1/2 [38]	1-5/16 [33]	1-5/16 [33]
Z9A-MA-2	2 [51]	1-11/32 [34]	1-9/16 [40]
Z9A-MA-3	3 [76]	2-5/32 [55]	2-13/16 [71]
Z9A-MA-4	4 [102]	2-1/16 [52]	3-1/32 [77]

## Z9A-FA FEMALE THREAD ADAPTER (NPT)

### Engineering Specification:

ASTM-F1412, F.R.P.P. - 210  
 ZURN Z9A-FA FEMALE ADAPTER – Flame-retardant polypropylene female thread adapter fitting assembly.  
 Use Teflon tape on threads.



**Note:** All sizes also available in straight thread.  
 Designate Z9A-FAS when ordering.

### Options:


-F Fusion Lock; -M Mechanical Seal; -S Stab•Lock Seal

Model No.	Dimensions in Inches [mm]		
	Nom. Pipe Size	E	L
Z9A-FA-112	1-1/2 [38]	7/32 [6]	2 [51]
Z9A-FA-2	2 [51]	5/32 [4]	2-7/32 [56]
Z9A-FA-3	3 [76]	5/16 [8]	3-9/16 [90]
Z9A-FA-4	4 [102]	11/32 [9]	3-21/32 [93]

## Z9A-GA GLASS PIPE ADAPTER

### Engineering Specification:

ASTM-F1412, F.R.P.P. - 210  
 ZURN Z9A-GA GLASS PIPE ADAPTER – Flame-retardant polypropylene glass adapter fitting assembly.



### Options:

-F Fusion Lock; -M Mechanical Seal; -S Stab•Lock Seal

Model No.	Dimensions in Inches [mm]		
	Nom. Pipe Size	E	L
Z9A-GA-112	1-1/2 [38]	31/32 [25]	2-1/16 [52]
Z9A-GA-2	2 [51]	1-3/16 [30]	2-1/2 [63]
Z9A-GA-3	3 [76]	1-31/32 [50]	3-9/16 [90]
Z9A-GA-4	4 [102]	2 [51]	3-9/16 [90]