

NR3XL Pressure Reducing Valve

Water Pressure Control for Residential Applications



The NR3XL Pressure Reducing Valve provides reliable pressure reduction for residential applications, and is available with a variety of end connections for installation versatility.

Durable Design

• Composite cartridge and bell housing offers superior strength and corrosion resistance

Installation Versatility

- Compact design with short lay length allows installation in tight spaces
- Labor saving tailpiece options include: PEX, threaded, copper sweat, CPVC, Z-Bite™ and Z-Press™ solderless connections, and more
- 1/4" gauge option for easy pressure adjustment after installation



Ease of Maintenance

- Threaded bell speeds access to cartridge internals
- Cartridge loaded design is easily repaired
- Readily available and affordable repair kits for lowest life-cycle costs

NR3XL Pressure Reducing Valve

Å	CONNECTION/TAILPIECE OPTIONS	SUFFIX	1/2"	3/4"	1"	1-1/4"	1-1/2"	2"
	FNPT Tailpiece (Standard)	-	~	~	~	~	~	~
	Integral FNPT Connection (Less Unions)	DULU	~	~	~	~	~	~
	Copper Sweat	С	~	~	~	~	~	~
	PEX	PEX	~	~	~			
	PEX ASTM F1960	PEXF1960	~	~	~			
	CPVC	CPVC	~	~	~			
	Z-Bite Push Type Solderless Connection	PF	~	~	~			
	Integral Z-Bite™ Push Type Solderless Connection (Less Unions)	DULUPF	~	~	~			
	Z-Press Press™ Type Solderless Connection	PR	~	~	~	~	~	~
	Integral Z-Press Push Type Solderless Connection (Less Unions)	DULUPR	~	~	~	~	~	~
	Copper Replacement Tailpiece	CR	~	~	~	~	~	~

Accessories

PART NUMBER	DESCRIPTION	SIZE
RKNR3XL	Repair Kit	
SPKNR3	FNPT x FNPT Spacer Kit	3/4", 1-1/4"-2"
SPKNR3C	Female CU SWT x Female CU SWT Spacer Kit	3/4", 1-1/4"-2"
SXL	Bronze Wye Type Strainer	1/2"-2"
92-25	Pressure Gauge	1/4"

Approvals

- ASSE® Listed 1003
- IAPMO® Listed
- CSA® Certified
- Meets the requirements of NSF/ANSI 61

