

MODEL ZW204 - Non-Modulating Float Valve Control Valve Order Form



Customer:	Date:
Contact:	Email:
Telephone/Fax:	Ref. P. O.

Required Valve Information

Quantity: _____

All returns are subject to a restocking/refurbishing fee.
Contact Customer Care for details on return policies.

Caution: The recommended installation orientation for ACVs is horizontal, with the valve cover up. 6" and larger valves should only be installed horizontally, with the valve cover up, due to the difficulty of properly bleeding air out of the cover and performing maintenance on valves installed in the vertical orientation.

Size: (Check one) 1-1/4" 1-1/2" 2" 2-1/2" 3" 4" 6" 8" 10" 12" 14" 16"

Function Options:

- Check all that apply
- "C" Option * - Check Valve with Isolation Valve
 - "L" Option * - Closing Speed Control (Standard on 8" and larger)
 - "O" Option * - Opening Speed Control

Valve body is ductile iron, epoxy coated

Body Options:

- Check one
- Standard - Full Port Globe Body
 - "A" Option - Angle Style Body (1-1/4" - 10")
 - "R" Option - Reduced Port Body (3" - 10" Flanged only)

End Connections:

- Check one
- Standard - ANSI Class 150 Flanges (1-1/2" - 16")
 - "G" Option - IPS Grooved (1-1/2" - 10")
 - "TH" Option - NPT Threaded (1-1/4" - 3")
 - "Y" Option * - ANSI Class 300 Flanges (1-1/2" - 16")

Main Valve Options:

- Check all that apply
- Standard - Stainless Steel Seat, Seal Ring Retainer and Stem Guide
 - "V" Option * - Viton Rubber Internals, Rated 180°F (1-1/4" - 6")
 - "Z" Option *¹ - Visual Position Indicator
 - "SO" Option *¹ - Limit Switch Open Trip
 - "SC" Option *¹ - Limit Switch Closed Trip
 - "SD" Option *¹ - Limit Switch Dual Trip

Pilot Options:

- Check all that apply
- Standard - Isolation Valves, and "Wye" Type Strainer
 - Standard - Copper Tubing and Brass Fittings
 - "SP" Option * - All Stainless Steel Pilotry (replaces all Brass Fittings & Copper Tubing. "GL" Option included)
 - "SH" Option * - Stainless Steel Braided Hoses (replaces Copper Tubing, with "VM" Option only)

Must check one

- Standard - Remotely Mounted Float
- "VM" Option * - Valve Mounted Float SEE IMAGES

Check one

- Standard - 2' Standard Float Rod (Stainless Steel Rod & Float)
- "R1" Option * - 1' Float Rod Extension (3' total length)
- "R2" Option * - 2' Float Rod Extension (4' total length)
- "R3" Option * - 3' Float Rod Extension (5' total length)

Optional

- "RV" Option * - Pilot Installed on Reverse Side

*Adder to standard price applies ¹ Limit switch and position indicator options cannot be combined



DIRECTION OF FLOW ⇒

STANDARD - REMOTELY MOUNTED
MOUNTED FLOAT



DIRECTION OF FLOW ⇒

("VM" OPTION)

1747 Commerce Way
Paso Robles, CA 93446
Phone: 855-663-9876
Fax: 805-237-7197

Customer Service Representatives available
Monday through Friday 5:30 a.m. to 5:00 p.m., PST
Fax completed forms to 805-237-7197, attention: Sales
Call 855-663-9876, wilkinscs@zurn.com
or visit us online at www.zurn.com

