

MODEL ZW204FP - Non-Modulating Float Valve

Control Valve Order Form



| | |
|----------------|------------|
| Customer: | Date: |
| Contact: | Email: |
| Telephone/Fax: | Ref. P. O. |

Required Valve Information

Quantity: _____

All returns are subject to a restocking/refurbishing fee.
Contact Customer Care for details on return policies.

Size: (Check one) 1-1/4" 1-1/2" 2" 2-1/2" 3" 4" 6" 8" 10"

Caution: The recommended installation orientation for ACVs is horizontal, with the valve cover up. 6" and larger valves should only be installed horizontally, with the valve cover up, due to the difficulty of properly bleeding air out of the cover and performing maintenance on valves installed in the vertical orientation.

Function Options:

- | | | |
|----------------------|--------------|---|
| Check all that apply | "C" Option * | - Check Valve with Isolation Valve |
| | "L" Option * | - Closing Speed Control (Standard on 8" and larger) |
| | "O" Option * | - Opening Speed Control |

Valve body is ductile iron, epoxy coated

Body Options:

- | | | |
|-----------|------------|---|
| Check one | Standard | - Full Port Globe Body |
| | "A" Option | - Angle Style Body (1-1/4" - 10") |
| | "R" Option | - Reduced Port Body (3" - 10" Flanged only) |

End Connections:

- | | | |
|-----------|--------------|---|
| Check one | Standard | - ANSI Class 150 Flanges (1-1/2" - 16") |
| | "G" Option | - IPS Grooved (1-1/2" - 10") |
| | "TH" Option | - NPT Threaded (1-1/4" - 3") |
| | "Y" Option * | - ANSI Class 300 Flanges (1-1/2" - 16") |

Main Valve Options:

- | | | |
|----------------------|--------------|---|
| Check all that apply | Standard | - Stainless Steel Seat, Seal Ring Retainer and Stem Guide |
| | "V" Option * | - Viton Rubber Internals, Rated 180°F (1-1/4" - 6") |
| | "Z" Option * | - Visual Position Indicator |

Pilot Options:

- | | | |
|----------------------|---------------|---|
| | Standard | - "Wye" Type Strainer |
| Check all that apply | Standard | - Copper Tubing and Brass Fittings |
| | "SP" Option * | - All Stainless Steel Pilotry (replaces all Brass Fittings & Copper Tubing. "GL" Option included) |
| | "SH" Option * | - Stainless Steel Braided Hoses (replaces Copper Tubing, with "VM" Option only) |
| Must check one | Standard | - Remotely Mounted Float |
| | "VM" Option * | - Valve Mounted Float Pilot SEE IMAGES |
| Check one | Standard | - 2' Standard Float Rod (Stainless Steel Rod & Float) |
| | "R1" Option * | - 1' Float Rod Extension (3' total length) |
| | "R2" Option * | - 2' Float Rod Extension (4' total length) |
| | "R3" Option * | - 3' Float Rod Extension (5' total length) |
| Optional | "RV" Option | - Pilot Installed on Reverse Side |



STANDARD - REMOTELY MOUNTED FLOAT



DIRECTION OF FLOW =>
("VM" OPTION)

*Adder to standard price applies

1747 Commerce Way
Paso Robles, CA 93446
Phone: 855-663-9876
Fax: 805-237-7197

Customer Service Representatives available
Monday through Friday 5:30 a.m. to 5:00 p.m., PST
Fax completed forms to 805-237-7197, attention: Sales
Call 855-663-9876, wilkinscs@zurn.com
or visit us online at www.zurn.com



Document# Rev. B

OF-ZW204FP Date: 5/23