

Model ZW209FP - Fire Protection Pressure Reducing Valve Control Valve Order Form



Customer:	Date:
Contact:	Email:
Telephone/Fax:	Ref. P. O.

Required Valve Information

Quantity: _____

All returns are subject to a restocking/refurbishing fee.
Contact Customer Care for details on return policies.

Size: (Check one) ☐ 1-1/4" ☐ 1-1/2" ☐ 2" ☐ 2-1/2" ☐ 3" ☐ 4" ☐ 6" ☐ 8" ☐ 10"

Caution: The recommended installation orientation for ACVs is horizontal, with the valve cover up. 6" and larger valves should only be installed horizontally, with the valve cover up, due to the difficulty of properly bleeding air out of the cover and performing maintenance on valves installed in the vertical orientation.

Function Options:

Optional ☐ "C" Option * - 40XL2 Hydraulic Check

Valve body is ductile iron, epoxy coated

Body Options:

Check one ☐ Standard - Full Port Globe Body
☐ "A" Option - Angle Style Body

End Connections:

Check one ☐ "G" Option - IPS Grooved (1-1/2" - 10")
☐ "TH" Option - NPT Threaded (1-1/4" - 3")
☐ "Y" Option - ANSI Class 300 Flanges (1-1/2" - 10")
☐ "X" Option - ANSI Class 150 Flanges (1-1/2" - 10")



DIRECTION OF FLOW →

Main Valve Options:

☒ Standard - Stainless Steel Seat, Seal Ring Retainer, and Stem Guide
Optional: ☐ "Z" Option * - Visual Position Indicator (Not available with SP pilot)
Check Z OR Z2 ☐ "Z2" Option * - Stainless Steel Dry Position Indicator

Pilot Options:

☒ Standard - 3-Way Gauge Isolation Valves, Inlet and Outlet Pressure Gauges (UL), and "Wye" Type Strainer
☒ Standard - PV-PRD Pilot (50 - 165 psi) (155 psi Max 10")
Check one ☐ Standard - Copper Tubing and Brass Fittings
☐ "SP" Option * - All Stainless Steel Pilotry (replaces all Brass Fittings, Pilot Valve & Copper Tubing)



DIRECTION OF FLOW →

Optional ☐ "RV" Option - Pilot on Reverse Side

UL & C-UL LISTED: 1-1-1/4" - 10"

***Adder to standard price applies**

1747 Commerce Way
Paso Robles, CA 93446
Phone: 855-663-9876
Fax: 805-237-7197

Customer Service Representatives available
Monday through Friday 5:30 a.m. to 5:00 p.m., PST
Fax completed forms to 805-237-7197, attention: Sales
Call 855-663-9876, wilkinscs@zurn.com
or visit us online at www.zurn.com

