

MODEL ZW209FPHP- Fire Protection Pressure Reducing Valve Control Valve Order Form



Customer:	Date:
Contact:	Email:
Telephone/Fax:	Ref. P. O.

Required Valve Information

Quantity: _____

All returns are subject to a restocking/refurbishing fee.
Contact Customer Care for details on return policies.

Size: (Check one) ☐ DN32 ☐ DN40 ☐ DN50 ☐ DN65 ☐ DN80 ☐ DN100 ☐ DN150 ☐ DN200 ☐ DN250

Caution: The recommended installation orientation for ACVs is horizontal, with the valve cover up. 6" and larger valves should only be installed horizontally, with the valve cover up, due to the difficulty of properly bleeding air out of the cover and performing maintenance on valves installed in the vertical orientation.

Function Options:

Optional ☐ "C" Option* - 40XL2 Hydraulic Check

Valve body is ductile iron, epoxy coated

Body Options:

Check one ☐ Standard - Full Port Globe Body
☐ "A" Option - Angle Style Body

End Connections (Check one)

Options Description

- ☐ "X" - ANSI Class 150 Flanges
- ☐ "BSD" - BS10/AS2129 Table D Flanges
- ☐ "BSE" - BS10/AS2129 Table E Flanges
- ☐ "BSF"* - BS10/AS2129 Table F Flanges
- ☐ "BSH"* - BS10/AS2129 Table H Flanges
- ☐ "G" - IPS Grooved, ANSI/AWWA C 606
- ☐ "BG" - Grooved DN65, or DN150 (76.1 mm or 165.1mm pipe OD)
- ☐ "Y"* - ANSI Class 300 Flanges

Size Range (DN40 - DN250)

Options Description

- ☐ "PN6" - ISO Class PN6 Flanges
- ☐ "PN10" - ISO Class PN10 Flanges
- ☐ "PN16" - ISO Class PN16 Flanges
- ☐ "PN25"* - ISO Class PN25 Flanges

Size Range (DN32 - DN80)

- ☐ "TH" - NPT Threaded, ANSI/ASME B1.20.1
- ☐ "BS" - Threaded British Pipe Parallel BSPP/G size ISO
- ☐ "BT" - Threaded British Pipe Tapered BSPT/Rc size ISO

Main Valve Option:

- ☒ Standard - Stainless Steel Seat, Seal Ring Retainer, and Stem Guide
- Optional: ☐ "Z" Option* - Visual Position Indicator (Not available with SP pilot)
- Z OR Z2 ☐ "Z2" Option* - Stainless Steel Dry Position Indicator

Pilot Options:

- ☒ Standard - 3-Way Gauge Isolation Valves, Inlet and Outlet Pressure Gauges (UL) and "Wye" Type Strainer
 - ☒ Standard - "HP Option" (205-2050kPa)
-
- Check one ☐ Standard - Copper Tubing and Brass Fittings
☐ "SP" Option* - All Stainless Steel Pilotry (replaces all Brass Fittings, Pilot Valve & Copper Tubing)


Optional ☐ "RV" Option - Pilot on Reverse Side

Note: Valves with set pressure above 1200 kPa cannot be UL Listed

*Adder to standard price applies



DIRECTION OF FLOW ⇒



DIRECTION OF FLOW ⇒

1747 Commerce Way
Paso Robles, CA 93446
Phone: 855-663-9876
Fax: 805-237-7197

Customer Service Representatives available
Monday through Friday 5:30 a.m. to 5:00 p.m., PST
Fax completed forms to 805-237-7197, attention: Sales
Call 855-663-9876, wilkinscs@zurnwilkins.com
or visit us online at www.zurn.com



Document#

Rev. E

OF-ZW209FPHP-INT(mm)

Date: 5/23