

MODEL ZW209H - Pressure Reducing and Pressure Sustaining Valve

Control Valve Order Form



Customer:	Date:
Contact:	Email:
Telephone/Fax:	Ref. P. O.

Required Valve Information

Quantity: _____

All returns are subject to a restocking/refurbishing fee.
Contact Customer Care for details on return policies.

Size: (Check one) 1-1/4" 1-1/2" 2" 2-1/2" 3" 4" 6" 8" 10" 12" 14" 16"

Caution: The recommended installation orientation for ACVs is horizontal, with the valve cover up. 6" and larger valves should only be installed horizontally, with the valve cover up, due to the difficulty of properly bleeding air out of the cover and performing maintenance on valves installed in the vertical orientation.

Function Options:

- Check all that apply
- "C" Option *** - Check Valve with Isolation Valve
 - "L" Option *** - Closing Speed Control
 - "O" Option *** - Opening Speed Control (Standard on 4" or smaller)

Valve body is ductile iron, epoxy coated

Body Options:


- Check one
- Standard** - Full Port Globe Body
 - "A" Option** - Angle Style Body (1-1/4" - 10")
 - "R" Option** - Reduced Port Body (3" - 10" Flanged only)

End Connections:

- Check one
- Standard** - ANSI Class 150 Flanges (1-1/2" - 16")
 - "G" Option** - IPS Grooved (1-1/2" - 10")
 - "TH" Option** - NPT Threaded (1-1/4" - 3")
 - "Y" Option *** - ANSI Class 300 Flanges (1-1/2" - 16")

Main Valve Options:

- ☒ Check all that apply
- Standard** - Stainless Steel Seat, Seal Ring Retainer, and Stem Guide
 - "Z" Option *1** - Visual Position Indicator
 - "SO" Option *1** - Limit Switch Open Trip
 - "SC" Option *1** - Limit Switch Closed Trip
 - "SD" Option *1** - Limit Switch Dual Trip



Pilot Options:

MUST CHECK ONE REDUCING BOX & ONE SUSTAINING PRESSURE RANGE BOX

SUSTAINING→		LP3 5 - 15 psi	LP2 10 - 35 psi	LP 30 - 90 psi	S 50 - 200 psi	HP 150 - 300 psi
↓ REDUCING	LP*	LPLP3	LPLP2	LPLP	LPS	LPHP
	S	SLP3	SLP2	SLP	(no adder)	SHP
	HP*	HPLP3	HPLP2	HPLP	HPS	HPHP

- ☒ Check all that apply
- Standard** - Isolation Valves, Inlet and Outlet Pressure Gauges, and "Wye" Type Strainer
 - Standard** - Copper Tubing and Brass Fittings
 - "SP" Option *** - All Stainless Steel Pilotry (replaces all Brass Fittings, Pilot Valve & Copper Tubing. "GL" Option included)
 - "SH" Option *** - Stainless Steel Braided Hoses (only replaces Copper Tubing)
 - "RV" Option** - Pilot Installed on Reverse Side
 - "GL" Option *** - Liquid Filled Pressure Gauge

*Adder to standard price applies

*Limit switch and position indicator options cannot be combined

1747 Commerce Way
Paso Robles, CA 93446
Phone: 855-663-9876
Fax: 805-237-7197

Customer Service Representatives available
Monday through Friday 5:30 a.m. to 5:00 p.m., PST
Fax completed forms to 805-237-7197, attention: Sales
Call 855-663-9876, wilkinscs@zurn.com
or visit us online at www.zurn.com



Document# Rev. L

OF-ZW209H 9/23