



Z6003AV

Exposed Flush Valve for Urinals

TAG _____

Architectural/Engineering Specification:

Exposed, quiet diaphragm-type, chrome plated flushometer valve with a polished exterior. Complete with Zurn's AquaVantage® TPE, chloramine resistant, dual seal diaphragm with a clog resistant, triple filtered by-pass. The valve is ADA compliant with a non-hold open and no leak handle feature. Internal seals are made of chloramine resistant materials.

Product Features:

- Proprietary Dezincification resistant low lead brass alloy
- Control Stop has internal siphon-guard protection and vandal resistant stop cap, Sweat solder kit, wall flange with set screw.
- High back pressure vacuum breaker with one piece hex coupling nut
- Chloramine resistant Internal seals
- Adjustable tailpiece
- Spud coupling and flange for top spud connection

Valve Height Options:

Product No.	A
Z6003AV	11 1/2" [292]
Z6003AV-1	16" [406]
Z6003AV-2	24" [610]
Z6003AV-3	27" [686]

Compliance and Certification:

- ADA Compliant



*This product should be used with a WaterSense labeled counterpart with a compatible flow volume to ensure that the entire system meets the requirements for water efficiency and performance.



Flow Options:

	Flush Volume	WaterSense* Labeled
-ULF	0.125 gpf	✓
-EWS	0.5 gpf	✓
-WS1	1.0 gpf	

Suffix Options:

- BG BioCare Handle
- D1 1" Supply
- L 1" [25] Metal Push Button
- L3 3" [76] Metal Push Button
- YJ Split Ring Pipe Support
- YK Solid Ring Pipe Support

**Not available with triple filter by-pass

Architectural/Engineering Approval

The information contained in this document is subject to change without notice. Please contact Zurn for most up to date information.



Z6003AV

Exposed Flush Valve for Urinals

TAG _____

Rough-in/Overview dimensions

