



# ZER6153AV

## Battery Powered Automatic Sensor Flush Valve For Water Closets

TAG \_\_\_\_\_

### Architectural/Engineering Specification:

Concealed, quiet diaphragm-type, rough brass flushometer valve. Complete with Zurn's AquaVantage® TPE, chloramine resistant, dual seal diaphragm with a clog resistant, triple filtered by-pass. The valve incorporates a 6VDC motor actuator, a battery powered automatic sensor, high impact resistant polycarbonate housing and chrome plated plastic cover with manual override push button. Switchable sensor features include 24 hour auto flush and diagnostic indicator lights.

### Product Features:

- Proprietary Dezincification resistant low lead brass alloy
- Control Stop has internal siphon-guard protection and Sweat solder kit.
- High back pressure Vacuum Breaker with one piece hex coupling nut
- Chloramine resistant Internal seals
- Adjustable tailpiece
- Spud coupling and flange for back spud connection

### Compliance and Certification:

- ADA Compliant



\*This product should be used with a WaterSense labeled counterpart with a compatible flow volume to ensure that the entire system meets the requirements for water efficiency and performance.



### Flow Options:

	Flush Volume	WaterSense* Labeled
<b>-ONE**</b>	1.1 gpf	✓
<b>-HET**</b>	1.28 gpf	✓
<b>-WS1</b>	1.6 gpf	
<b>-Standard</b>	3.5 gpf	

\*\* Not available with triple filter by-pass

### Suffix Options:

- CCP Complete Chrome Plastic
- CPM Chrome Plated Metal

Architectural/Engineering Approval

The information contained in this document is subject to change without notice. Please contact Zurn for most up to date information.



# ZER6153AV

Battery Powered Automatic Sensor Flush Valve  
For Water Closets

TAG \_\_\_\_\_

## Rough-in/Overview dimensions

