### **Architectural/Engineering Specification:**

Polished chrome-plated single lavatory, slow-closing metering faucet with an integral brass 3-3/4" centerline spout, and a vandal-resistant, ADA compliant color-coded handle. Easily adjustable cycle time, preset to 10 seconds at 80 PSI. Unit is furnished with a standard water-conserving 1.0 GPM spray outlet, integral shank filter, mounting hardware and a 1/2" NPSM coupling nut for standard lavatory riser. Requires less than 5 pounds force to activate per ANSI A117.1.

Zurn Lead Free products (-XL) is the line of durable, high quality brass faucets and fixtures that are designed and manufactured to comply with Section 1417 of the Safe Drinking Water Act (SDWA) which mandates the weighted average lead content of no more than 0.25% of the wetted surface.

#### **Product Features:**

- · Polymer Metering Cartridge Sleeve
- · Chrome-plated Cast Brass Body
- Vandal-resistant
- · Color Coded Brass Metering Handle
- · Adjustable Cycle Timing

#### **Compliance and Certification:**

- · Low-Lead Compliant
- ADA Compliant



## **Aerator Options:**

	Flow rate GPM [LpM]	Vandal Resistant	Pressure Compensation	Outlet Type
-3M	0.5[1.9]	✓	✓	Spray
-7M	1.0[3.8]		✓	Spray
-16M	1.0[3.8]	✓	✓	Spray
-22M	1.0[3.8]	<b>✓</b>		Laminar
-25M	0.35[1.3]	<b>✓</b>	✓	Spray
-28M	0.5[1.9]	✓		Laminar

# **Suffix Options:**

Check Stop
Chrome Plated 4" Cover Plate
1-1/4" [32mm] Grid Strainer Drain
Institutional handle - Tamper Proof and
Vandal Resistant
ADA Cmpliant Rocker Handle

**Architectural/Engineering Approval** 

The information contained in this document is subject to change without notice. Please contact Zurn for most up to date information.



TAG \_\_\_\_\_

### Rough-in/Overview dimensions

