



TAG \_\_\_\_\_

**ARCHITECTURAL & ENGINEERING SPECIFICATION**

Complete EcoVantage® high efficiency 1.1 gpf manual actuated wall mounted commercial water closet system with Z6000AV-ONE exposed, manually activated chrome-plated closet diaphragm flushometer for either left or right hand supply, Z5955SS-EL open front commercial toilet seat, Z5615-BWL wall mounted vitreous china water closet with Z5977-NEO NeoSeal outlet sealing gasket assembly kit and Z5610-NUT-EXT-KIT manufactured by Zurn.

**PRODUCT FEATURES**

- 1.1 gpf (gallons per flush)
- Wall mounted elongated front rim top spud toilet
- High efficiency siphon jet flush action
- 2-1/8" fully glazed trapway
- Large water spot - 12' x 10'
- Vitreous china wall bowl construction
- Static weight load of 1000 lb\*  
\*Not intended for bariatric use
- Diaphragm- type flushometer complete with Zurn's Go Blue® TPE, chloramine resistant, dual seal diaphragm with a clog resistant filtered bypass
- ADA compliant, non-hold open, dual seal handle
- High pressure vacuum breaker
- Adjustable tailpiece
- Control stop with internal siphon guard protection, vandal resistant cap, sweat solder kit and cast wall flange with set screw
- Open front, elongated, white commercial toilet seat with SS check hinges
- NeoSeal® outlet gasket assembly
- 14% water savings over standard 1.28 gpf system
- 31% water savings over standard 1.6 gpf system

**COMPLIANCE AND CERTIFICATION:**

- Meets the American Disabilities Guidelines and ANSI A117.1 requirements when installed according to these requirements.
- Fixture - Complies with ASME A112.19.2 / CSA B45.1
- Flush Valve - Complies with ASSE 1037 / ASME A112.1037 / CSA B125.37



This product should be used with a WaterSense labeled counterpart with a compatible flow volume to ensure that the entire system meets the requirements for water efficiency and performance.



**ZURN ONE SYSTEM PACKOUT INCLUDES:**

**Z5615-BWL:**

Vitreous China, 1.1 gpf [4.2 Lpf] or greater high efficiency wall hung toilet with siphon jet flushing action and elongated front rim with 1-1/2" [38mm] top spud

**Z6000AV-ONE:**

Exposed, quiet diaphragm-type, chrome-plated flushometer valve with a polished exterior. Complete with Zurn's AquaVantage® TPE, chloramine resistant, dual seal diaphragm with a clog resistant, filtered bypass. The valve is ADA compliant with a non-hold open and no leak handle feature. Internal seals are made of chloramine resistant materials

**Z5955SS-EL:**

Elongated, open front white toilet seat with stainless steel check hinges

**Z5610-NUT-EXT-KIT:**

Retrofit nut kit for extending carrier studs from existing wall

**Z5977-NEO:**

NeoSeal® gasket kit for wall mounted bowls


**RECOMMENDED CARRIER:**

Z1201 or Z1202 EZCarry™      500 lbs load rated High Efficiency Carrier



The information contained in this document is subject to change without notice. Please contact Zurn for most up to date information.

Rough-in / Overview dimensions



\*NOTE: For ADA compliance, top of seat height should be installed at 17" [431mm] -19" [482mm] from finished floor.