

### Architectural/Engineering Specification:

Zurn HYDRO-X Power sensor faucets are ideal for high-use applications where **sustainable power**, **durability** and **hands-free operation** are necessary. Self-sustaining hydropower with battery backup for ten years of trouble-free operation, ADA compliant, polished chrome-plated cast brass sensor faucet with infrared proximity sensor for retrofit and new construction. Unit is furnished with a standard 0.5 GPM flow control and mounting hardware.

Zurn Lead Free products (-XL) is the line of durable, high quality brass faucets and fixtures that are designed and manufactured to comply with Section 1417 of the Safe Drinking Water Act (SDWA) which mandates the weighted average lead content of no more than 0.25% of the wetted surface.

### Product Features:

- Self Sustaining Hydropower for 10+ years operation
- Battery Backup
- Infrared convergence-type proximity sensor
- 30 second time out feature
- Chrome-plated Cast Brass Body
- In-line filter
- 4 "AA" batteries
- Inlet for a 1/2" ball riser

### Suffix Options:

- FC Flow Control in base of Spout
- GA 3-1/2" Goosneck Spout
- GC 8" Goosneck Spout
- MV Temperature Mixing Valve
- SH Supply Hoses for Mixing Valve
- TMV-1 Thermostatic Mixing Valve for Single Faucets

### Compliance and Certification:

- Lead Free Compliant
- ADA Compliant
- Complies with ASME A112.18.1 / CSA B125.1



\*This device is WaterSense labeled when used with the appropriate flow rate and certified for residential and private restrooms.



### Aerator Options:

|           | Flowrate<br>GPM [LpM] | Vandal<br>Resistant | WaterSense*<br>Labeled | Outlet Type |
|-----------|-----------------------|---------------------|------------------------|-------------|
| <b>-E</b> | 1.5[5.7]              | ✓                   | ✓                      | Aerator     |
| <b>-F</b> | 0.5[1.9]              | ✓                   |                        | Spray       |
| <b>-J</b> | 1.5[5.7]              | ✓                   | ✓                      | Laminar     |
| <b>-K</b> | 1.0[3.8]              | ✓                   | ✓                      | Laminar     |
| <b>-L</b> | 1.0[3.8]              | ✓                   |                        | Aerator     |
| <b>-M</b> | 0.35[1.3]             | ✓                   |                        | Spray       |
| <b>-N</b> | 0.5[1.9]              | ✓                   |                        | Laminar     |

**Architectural/Engineering Approval**

The information contained in this document is subject to change without notice. Please contact Zurn for most up to date information.

**TYPICAL Z6922-XL-HYD**

**Self Sustaining Battery Powered  
Faucet**

Recommended through hole diameter to properly mount the spout/shank is 1-1/8" to 1-1/4".

