

### ARCHITECTURAL/ENGINEERING SPECIFICATION

Polished chrome-plated cast brass faucet body with integral shanks, quarter turn ceramic disc cartridges and a 5-3/8" rigid or swing spout. Unit is furnished with a standard 2.2 GPM aerator, vandal-resistant color-coded handles, mounting hardware and 1/2" NPSM coupling nuts for standard lavatory risers.

Zurn Lead Free products (-XL) is the line of durable, high quality brass faucets and fixtures that are designed and manufactured to comply with Section 1417 of the Safe Drinking Water Act (SDWA) which mandates the weighted average lead content of no more than 0.25% of the wetted surface.

### PRODUCT FEATURES

- Ceramic Disc Cartridge
- Chrome-plated Cast Brass Body
- 4" Vandal Resistant Color Coded Wrist Blade Handles

### SUFFIX OPTIONS

- FC 2.0 GPM [7.6 L] Laminar Flow Control in Base of Spout
- FC \_\_\_\_\_ Plain End Spout with Flow Control (Specify GPM Flow: 0.5, 1.0, 1.5)
- 140 Restricted 140° Swing Spout

### COMPLIANCE AND CERTIFICATION

- Low-Lead Compliant
- ADA Compliant



\*This device is WaterSense labeled when used with the appropriate flow rate and certified for residential and private restrooms.



### AERATOR OPTIONS

	FLOWRATE GPM [LPM]	VANDAL RESISTANT	PRESSURE COMPRESSION	WATER SENSE LABELED	OUTLET TYPE
<b>-2F</b>	2.2 [8.3]	☑	☑		Aerator
<b>-3F</b>	0.5 [1.9]	☑	☑		Spray
<b>-4F</b>	2.2 [8.3]	☑	☑		Laminar
<b>-5F</b>	2.0 [7.6]	☑	☑		Aerator
<b>-7F</b>	1.0 [3.8]		☑	☑	Spray
<b>-16F</b>	1.0 [3.8]	☑	☑		Spray
<b>-17F</b>	1.5 [5.7]	☑	☑	☑	Aerator
<b>-18F</b>	1.5 [5.7]	☑	☑	☑	Laminar
<b>-22F</b>	1.0 [3.8]	☑			Laminar
<b>-25F</b>	0.35 [1.3]	☑	☑		Spray
<b>-28F</b>	0.5 [1.9]	☑			Laminar
<b>-FC0.5</b>	0.5 [1.9]		☑		Plain End
<b>-FC1.0</b>	1.0 [3.8]		☑	☑	Plain End
<b>-FC1.5</b>	1.5 [5.7]		☑	☑	Plain End
<b>-FC</b>	2.0 [7.6]		☑		Plain End

#### Architectural/Engineering Approval

The information contained in this document is subject to change without notice. Please contact Zurn for most up to date information.

ROUGH-IN/OVERVIEW DIMENSIONS

