

TAG			
IAG			

#### ARCHITECTURAL/ENGINEERING SPECIFICATION

The ZER EZ Gear-Driven Urinal Retrofit Kit is performance engineered with the dual action of the ceramic disc cartridge and motor gear-driven operation. Its polished chrome-plated finish, modern top-mount design, and quiet diaphragm operation are ideal for new and retrofit commercial restroom applications.

#### **PRODUCT FEATURES**

- Zurn's TPE diaphragm Clog-resistant bypass Chloramine resistant
- Actuator
   Electronic automatic sensor
   Gear-driven ceramic cartridge
- True Mechanical Override Button
- · Chloramine-resistant internal seals
- Universal mounting kit supplied with threaded ring for Zurn and alternative manufacturers diaphragm valves
- Operating Pressure
   25 psi (running) 80 psi (static)
   Higher running pressure may be required for some fixtures. Consult fixture manufacturer for details.

## COMPLIANCE AND CERTIFICATION

ADA Compliant



## **FLOW OPTIONS**

	FLUSH VOLUME GPF
	FLU GPI
-ULF	0.125
-EWS	0.5
-WS1	1.0

### **SUFFIX OPTIONS**

- -S Valve Head with Sloan® Thread Locking Ring\*
- \* Sloan is a registered trademark of Sloan Valve Company. Sloan and the Sloan products listed are not associated with Zurn or Zurn's products.

The brands and product names listed may be subject to the trademark rights of their respective owners. Use of the brands and names is for identification purposes only and does not imply affiliation with or endorsement by Zurn. Zurn provides this information for general cross reference purposes only. Zurn makes no representations regarding the quality, comparability, or compatibility of any competitor products listed. All information is subject to change without notice.

ARCHITECTURAL & ENGINEERING APPROVAL

The information contained in this document is subject to change without notice. Please contact Zurn for most up to date information.

Rev. B | Date: 6/11/2025 | C.N. No. 146958 | Prod./Dwg. No. SS ZERK-U-\_\_-TM-MOB



TAG \_\_\_\_\_

# Rough-in dimensions/Overview dimensions



