

9. LIFETIME WARRANTY AGAINST LEAKS, AND STRUCTURAL FAILU DUE TO MANUFACTURING DEFECTS.

CONSULT LOCAL AUTHORITIES FOR MINIMUM SIZE OF SEPARATORS

Proceptor* Model No.: SEE NOTE 1
Flow Rate SEE NOTE 2 Inte: Size 100mm (4in)
Ext. Flow Control NO
Containment Cap: 507 kg (200 kg)
Removal Efficiency: B3 % Access BEE
Oover Load. Vor= 2
Greek Turde Technologies and the services was

PROCEPTOR NOMINAL TANK DIMENSIONS (INCHES)									
MODEL	VOLUME (US GAL)	GREASE CAPACITY (US GAL)	SOLIDS CAPACITY (US GAL)	PIPE SIZE (P)	INLET (A)	OUTLET (B)	BURIAL (C)	HEIGHT (D)	SKU
GMC 50 CSA	50	18	17	4	12	11	8	24	10030000
GMC 100 CSA	100	42	23	4	20	19	8	32	10130000
GMC 100 CSA	100	42	23	6	20	19	8	32	10130100
GMC 200 CSA	200	90	72	4	36	35	8	48	10330000
GMC 200 CSA	200	90	72	6	36	35	8	48	10330100
GMC 250 CSA	250	119	91	4	44	43	8	56	10430000
GMC 250 CSA	250	119	91	6	44	43	8	56	10430100
GMC 300 CSA	300	156	103	4	52	51	8	64	10530000
GMC 300 CSA	300	156	103	6	52	51	8	64	10530100

NOTES:

1. IF 6" PIPING IS ORDERED, INSTALLER IS RESPONSIBLE FOR INSTALLING THE PROVIDED 4" PVC FLOW CONTROL

