


- NOTES:
- CONCRETE TO BE 28 DAY COMPRESSIVE STRENGTH TO 4000 PSI.
 - NO. 4 REBAR (Ø 1/2") GRADE 60 STEEL PER ASTM A615; CONNECTED WITH TIE WIRE.
 - REBAR TO BE 2.5" FROM FACE OF CONCRETE.
 - REBAR SPACING 12" GRID, 4" SPACING AROUND ACCESS OPENINGS.
 - ALL PENETRATIONS TO BE SLEEVED OR HAVE SLIP CONNECTIONS.
 - MINIMUM 18" FROM TOP OF SLAB TO TOP OF TANK.
 - EXTEND COMPACTED BACKFILL A MINIMUM 3 FT. BEYOND ALL SIDES OF TANK.

TANK MODELS
OMC 500 UPC
OMC 750 UPC
OMC 1000 UPC
OMC 1300 UPC
OMC 1500 UPC



TITLE: H2O TRAFFIC LOADING SLAB FOR SINGLE ELLIPTICAL TANK ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SHOWN.		REV	DATE	DRAWN
PROJECT: WO:		1	OCTOBER 1, 2010	L. SIMKINS
✓ CONFIGURATION:		2	JULY 02, 2013	S. MANGAT
		3		
		4		
		5		
		6		
		7		
		8		
		9		
		10		
DRAWN BY: L. SIMKINS				
DRAWN DATE: OCTOBER 1, 2008				

greenturtle®

877 428 8187 US 877 966 9444 CAN
www.greenturtletech.com

SIZE	DWG. NO.	REV.
A	SINGLE SLAB TRIPLE ACCESS	2

SCALE: 1:35 DO NOT SCALE DRAWING SHEET 1 OF 1