

ZN1201-HD4

NARROW WALL BACK-TO-BACK WITH 13-9/32 [337] FRONT TO BACK EZCARRY® ADJUSTABLE HORIZONTAL HIGH PERFORMANCE SIPHON JET HUB AND SPIGOT WATER CLOSET CARRIER SYSTEM



ENGINEERING SPECIFICATION: ZURN ZN1201-HD4

EZCarry[®] Narrow Wall horizontal siphon jet water closet carrier system, with high performance Dura-Coated cast iron main fitting with hydro-mechanically optimized sweep, 4" [102 mm] hub & spigot connections, and extended 2" [51 mm] vent. Corrosion resistant, adjustable 3" [76 mm] dia. X 6" [152 mm] couplings with integral test caps, designed to increase flow velocity and line carry, and labor saving "Neo-Seal" bonded gaskets optimize flow performance while reducing installation steps. Complete system includes adjustable, gasketed faceplates; floor mounted foot supports; fixture bolts, trim, and stud protectors. EZCarry[®] narrow wall system complies with all applicable requirements of ASME A112.6.1M up to a 500 lbs [227 kg] maximum static load.

OPTIONS (Check/specify appropriate options)

ZN1201-HD4 4 [102] Hub and Spigot Back-to-Back Inlet (Double)

PREFIXES Z

D.C.C.I. System with Zurn ZZ Adjustable Coupling*

SUFFIXES

CC	Corrosion Resistant Cast Iron Coupling (2-1/4 to 12 [57 to 305])
CS	2-1/4 [57] Polymer Coupling with Integral Test Cap
G	Galvanized Cast Iron
JC	2 [51] Auxiliary Inlet with 1/8 [3] Blend
	Vandal-Proof Trim
50	Flush Valve Supply Support for Water Closets
* Regularly	furnished unless otherwise specified.

Zurn Industries, LLC | Specification Drainage Operation 1801 Pittsburgh Avenue, Erie, PA U.S.A. 16502 · Ph. 855-663-9876, Fax 814-454-7929 In Canada | Zurn Industries Limited 3544 Nashua Drive, Mississauga, Ontario L4V 1L2 · Ph. 905-405-8272, Fax 905-405-1292